



MODEL NUMBER	T.P.H.	H.P.	R.P.M.	"A" DIA.	"B" LENGTH	"C"	"D"	"E"	"F"	"G"	"H"	"J"	"K"	"L"	"M"	"N"
RS4060	50	7 1/2	14	4'-0"	6'-6"	11'-5"	2'-3"	1'-4"	2'-0"	5'-0"	0'-11"	1'-4"	6'-0 3/4"	1'-3"	0'-6"	5'-9"
RS4080	66	7 1/2	14	4'-0"	8'-6"	13'-5"	2'-3"	1'-4"	2'-0"	5'-0"	0'-11"	1'-4"	8'-0 3/4"	1'-3"	0'-6"	5'-10 1/2"
RS4010	85	7 1/2	14	4'-0"	10'-6"	15'-5"	2'-3"	1'-4"	2'-0"	5'-0"	0'-11"	1'-4"	10'-0 3/4"	1'-3"	0'-6"	6'-0"
RS5010	125	7 1/2	14	5'-0"	10'-6"	15'-5"	2'-9"	1'-4"	3'-0"	6'-0"	0'-11"	1'-4"	10'-0 3/4"	1'-3"	0'-6"	6'-6"
RS5012	150	7 1/2	14	5'-0"	12'-6"	17'-5"	2'-9"	1'-4"	3'-0"	6'-0"	0'-11"	1'-4"	12'-0 3/4"	1'-3"	0'-6"	6'-7 1/2"
RS6013	200	10	14	6'-0"	14'-0"	19'-7"	3'-3"	1'-9"	4'-0"	7'-0"	1'-1"	1'-4"	13'-6 3/4"	1'-3"	0'-6"	7'-7"
RS6060	250	10	14	6'-0"	16'-6"	22'-1"	3'-3"	1'-9"	4'-0"	7'-0"	1'-1"	1'-4"	16'-6 3/4"	1'-3"	0'-6"	7'-9"

T.P.H. IS BASED ON 80#/CU.FT. MATERIAL WEIGHT WITH 2% MOISTURE CONTENT, 3/8" x 3/4" SCREEN OPENINGS AND .192 SCREEN CLOTH WIRE DIAMETER. T.P.H. MAY VARY DEPENDING ON PERCENTAGE OF BOND, SAND GRAIN SIZE, MOISTURE CONTENT, TEMPERATURE AND OTHER SCREEN OPENING SIZES.